



Connect™ C3 grid

– for installations in corrosive environments

Connect C3 grid is used for more demanding environments. Together with Ecophon Hygiene™ product range, Ecophon offer a wide range of solutions where humidity levels are occasionally high and where frequent cleaning is required. Examples of applications are: kitchens, food and beverage industries, shower areas, swimming halls (under favourable and well controlled conditions), pharmaceutical and electronics industries, and in healthcare premises.

The body of Connect T24 Main runner C3 and Connect T24 Cross tee C3 is special treated steel with high corrosion resistance, and it's capped with galvanized and coated steel. Connect C3 grid has a self-repairing protection on cut edges. Ecophon also offer different trims and accessories in corrosion class C3.



Connect T24 Main runner C3



Connect T24 Main runner C3 with Connect Hygiene clip 20

TECHNICAL INFORMATION

ARTICLES

26339140 Connect T24 Main runner C3 3700 mm

26339141 Connect T24 Cross tee C3 1200 mm

26339142 Connect T24 Cross tee C3 600 mm



INFLUENCE OF CLIMATE The grid meets the demand of corrosion class C3 according to EN ISO 12944-2.



CLEANABILITY Wet cleaning and high pressure washing. Can withstand the use of common disinfection chemicals.



MECHANICAL PROPERTIES See table about Max live load and Min load bearing capacity and Functional demands, Mechanical properties at www.ecophon.com



INSTALLATION Detailed installation guide (IG) for the different systems, visit www.ecophon.com